

BEFORE START

NORMAL CHECKLIST AIRBUS REV 1.0.2 - FEBRUARY '24

APPROACH

		7.111.07.011
COCKPIT PREP COMPLETE		BRIEFING CONFIRMED
FUEL MSG	SENT	EXAM STATUS CHECKED
GEAR PINS and COVERS		LANDING DISTANCE CONFIRM
SIGNS Of		SEAT BELTS AS RQRD
ADIRS		BARO REF SET (BOTH)
FUEL QUANTITY	KG.LB	MINIMUM SET (BOTH)
T/O DATA	SET	ENG MODE SEL
BARO REF SE		ENG MODE SEE
		LANDING
WINDOWS / DOORS	(BOTH)	
BEACON	,	CABIN CREW ADVISED
		A/THRSPEED/OFF
THR LEVERS		AUTOBRAKE AS RQRD
PARKING BREAK	•	EXAM MEMO LDG NO BLUE
MOBILES OFF	F (BOTH)	- LDG GEAR DN
ONE ENGINE TAXI DEPT	NSIDER	- SIGNS ON
ONE ENGINE WAS BELLINGE	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	- CABIN READY (△)
AFTER START ANTI-ICE		- SPLRS ARM
ANTLICE	VS DODD	- FLAPS SET
ECAM STATUS		AFTER LANDING
PITCH TRIM	SET	FLAPS RETRACTED
RUDDER TRIM	ZERO	
		SPOILERS DISARMED
BEFORE TAKEOFF		APU AS RQRD
FLIGHT CONTROLS) (DOTLI)	RADAR OFF / STBY
		PREDICTIVE WINDSHEAR SYSTEM OFF
FLT INST CHECKED) (BOTH)	
BRIEFING CON	IFIRMED	ONE ENGINE TAXI ARR CONSIDER
FLAP SETTING CONF	(BOTH)	PACK 2 AS RQRD
V1. VR. V2 / FLX TEMP	. ,	
	. ,	PARKING
ATC		Y ELEC PUMP OFF
ECAM MEMO TO N	NO BLUE	APU BLEED AS RQRD
- AUTO BRK MAX		•
- SIGNS ON		ENGINES OFF
- CABIN READY (⊲)		SEAT BELTS OFF
- SPLRS ARM		EXT LT AS RQRD
- FLAPS T/O		FUEL PUMPS OFF
- TO CONFIG NORM		
TAKEOFF RWY CONFIRM		PARK BRK and CHOCKS AS RQRD
	` ,	COMPANY MOBILES ON
CABIN CREW		Consider HEAVY RAIN
TCAS TA C	R TA/RA	
ENG MODE SEL	AS RORD	SECURING THE AIRCRAFT
PACKS	-	BRAKE TEMPERATURE
7,101.0		
AFTER TAKEOFF / CLIMB		ADIRSOFF
LDG GEAR	UP	OXYGEN OFF
		APU BLEED OFF
FLAPS RET	RACTED	EMER EXIT LT OFF
PACKS	ON	SIGNS / NO SMOKING OFF
BARO REF SE	T (DOTU)	
DARO RLF	i (BOTTI)	APU AND BAT OFF
EMERGENCY EVACUATION		Consider COLD WEATHER
	TOP / ON	
AIRCRAFT / PARKING BRAKE		
AIRCRAFT / PARKING BRAKE S ATC (VHF 1)		
ATC (VHF 1)	. NOTIFY	
ATC (VHF 1)	. NOTIFY	
ATC (VHF 1) CABIN CREW (PA) ΔP (only if MAN CAB PR has been used) CHE	. NOTIFY	
ATC (VHF 1) CABIN CREW (PA) ΔP (only if MAN CAB PR has been used) CHE If not zero, MODE SEL on MAN, V/S CTL FULL UP	. NOTIFY ALERT ECK ZERO	
ATC (VHF 1) CABIN CREW (PA) ΔP (only if MAN CAB PR has been used) CHE If not zero, MODE SEL on MAN, V/S CTL FULL UP ENG MASTERS (ALL)	. NOTIFY . ALERT ECK ZERO	
ATC (VHF 1) CABIN CREW (PA) ΔP (only if MAN CAB PR has been used) CHE If not zero, MODE SEL on MAN, V/S CTL FULL UP	. NOTIFY . ALERT ECK ZERO	
ATC (VHF 1) CABIN CREW (PA) \triangle P (only if MAN CAB PR has been used) If not zero, MODE SEL on MAN, V/S CTL FULL UP ENG MASTERS (ALL) FIRE Pushbuttons (ALL: ENG and APU)	. NOTIFY . ALERT ECK ZERO OFF PUSH	
ATC (VHF 1) CABIN CREW (PA) \triangle P (only if MAN CAB PR has been used) If not zero, MODE SEL on MAN, V/S CTL FULL UP ENG MASTERS (ALL) FIRE Pushbuttons (ALL: ENG and APU) AGENTS (ENG and APU)	. NOTIFY . ALERT ECK ZERO OFF PUSH	
ATC (VHF1). CABIN CREW (PA). △P (only if MAN CAB PR has been used). CHE If not zero, MODE SEL on MAN, V/S CTL FULL UP ENG MASTERS (ALL). FIRE Pushbuttons (ALL: ENG and APU). AGENTS (ENG and APU). ■If Evacuation required:	. NOTIFY ALERT ECK ZERO OFF PUSH AS RQRD	TAKEOFF CG 10.5/17 20 22 24 26 28 30 32 34 36 38 40/43
ATC (VHF 1) CABIN CREW (PA) △P (only if MAN CAB PR has been used) CHE If not zero, MODE SEL on MAN, V/S CTL FULL UP ENG MASTERS (ALL) FIRE Pushbuttons (ALL: ENG and APU) AGENTS (ENG and APU) ■If Evacuation required: - EVACUATION	. NOTIFY ALERT ECK ZERO OFF PUSH AS RQRD	
ATC (VHF 1) CABIN CREW (PA) ΔP (only if MAN CAB PR has been used) If not zero, MODE SEL on MAN, V/S CTL FULL UP ENG MASTERS (ALL) FIRE Pushbuttons (ALL: ENG and APU) AGENTS (ENG and APU) If Evacuation required: - EVACUATION If Evacuation not required:	. NOTIFY ALERT ECK ZEROOFFPUSH AS RQRD	TAKEOFF CG 10.5/17 20 22 24 26 28 30 32 34 36 38 40/43 TRIM POS 2.5 2 1 0 1 2 2.5
ATC (VHF 1) CABIN CREW (PA) △P (only if MAN CAB PR has been used) CHE If not zero, MODE SEL on MAN, V/S CTL FULL UP ENG MASTERS (ALL) FIRE Pushbuttons (ALL: ENG and APU) AGENTS (ENG and APU) ■If Evacuation required: - EVACUATION	. NOTIFY ALERT ECK ZEROOFFPUSH AS RQRD	